

Masking Tapes Solvent



Item: 60 SN

Backing: Saturated Paper Medium Creping

Adhesive: Natural rubber solvent based

Colour: Ivory

- Suitable for industrial processes, building industry and painting
- It can be used up to 60°C (60 minutes)
- Suitable for many kinds of paint and surfaces



Material Information

Code	Width (mm)	Length (m)
60 SN	15, 19, 25, 38, 48, 50	50

Technical Information

Total Grammatore		Total Thickness		Adhesion to Steel Plate		Tensile Strength		Elongation	
80 gr/mq	± 10%	110µm	± 10%	200 gr/cm	± 10%	3,8 Kg/cm	± 10%	7 %	± 3%

Storage Conditions

- We recommend a storage temperature between 18 and 30 °C.
- The product should not be directly exposed to heat or humidity.
- The product should be conditioned to room temperature before use.

All the above mentioned values in Technical Informations are to be considered as average values of our standard production and cannot be taken as product specifications. The products can present a ±2% tolerance in width and length. We recommend all our customers to make sure that the products is acceptable through preliminary test.

Certified Systems

UNI-EN ISO 9001:2008 n° IT244111
 UNI-EN ISO 14001:2004 n° IT246656
 UNI-EN ISO 18001:2007 n° IT249944
 EMAS REGISTRATION n°IT001596

Revised: 01/12/2022

